Direct Computational Experiments in Fluid Mechanics Using Three-Dimensional Tensor Mathematics

Alexander Bogdanov

St. Petersburg State University St. Petersburg, Russia e-mail: IVVISBogdanov@gmail.com Alexander Degtyarev

St. Petersburg State University St. Petersburg, Russia e-mail: ABDegtyarev@gmail.com

Vasily Khramushin

Sakhalin Division of Science-Engineering Society of Shipbuilders named Alexey Krylov Yuzhno-Sakhalinsk, Russia e-mail: V.Khram@gmail.com

ABSTRACT

Architecture of a digital computing system determines the technical foundation of a unified mathematical language for exact arithmetic-logical description of phenomena and laws of continuum mechanics for applications in fluid mechanics and theoretical physics. Deep parallelization of the computing processes serves to the revival of application of functional programming at a new technological level. The efficiency of computations is provided by true reproduction of the fundamental laws of physics and continuum mechanics. Tensor formalization of numerical objects and computing operations serves to spatial interpolation of rheological state parameters and laws of the fluid mechanics as mathematical models in the local coordinates of the elementary numeric cells - large liquid particles. The proposed approach allows the use of explicit numerical scheme, which is an important condition for increasing the efficiency of the algorithms developed by numerical procedures with natural parallelism.

Keywords

Computational experiment, tensor mathematics, hydromechanics, continuum and corpuscular mechanics.

1. INTRODUCTION

The history of the Computational Fluid Dynamics (CFD) evolved in the vision rapid growth of computing resources availability and periodic assessments of how much tera- or exaflops might be sufficient to solve all the problems of this science using pretty archaic mathematical methods. That said, attempts of Russian scientists [1, 2] to go back to the formulation of the computational problem based upon the synthesis of initial physical principles and to approach computational experiments projecting from new positions and to go towards direct simulation of flows looked extremely dissonant. However, in-depth analysis of the purely physical problems in mathematical models creation and applied algorithms design in CFD was made as long ago as back in 1974 [3].

The first alarming signals sounded at the beginning of the century, when it turned out that most of the standard programs, if portable to servers with multicore processors at all, scale very poorly to say the least. At present, when most of computing complexes are heterogeneous, no ideas for the transfer of standard CFD programs onto them are noticeable. And the reason for this is clear – the problem of the dynamics of elementary volume and geometric aspects of the dynamics are related so strongly, that the amount of diverse

information that must be exchanged at each step of the calculation is comparable to the sheer volume of the data processed. And none of the hybrid processor is capable to cope with that. By now, it has become apparent that formal parallelism using vectorization of processing threads is lacking as there's a need for total control and hybrid fine-tuning of computation processes depending upon the physical condition of the liquids simulated. The development of continuous-corpuscular methods based on the "Large particles method" [2], leads to computational models of tensor mathematics with independent status control of each computational cell-liquid particle, for which the computational algorithms as well as functional logic of physical phenomena and processes synthesis is being provided by arithmetic logic cores operating in parallel, that exactly matches the trends in the development of computer technology at the requests for the graphic visualization of three-dimensional spatial phenomena and dynamic processes with them. It is the use of tensor algebra for the direct simulation of physical phenomena and processes as part of the generalized tensor mathematics that allows to effectively synthesize hydrodynamic and geometrical aspects of the computing process in general. It's long been understood in field theory. Such a program for quantum gravity was outlined in [4], and then brilliantly realized in [5]. CFD problems have the very same nature, thus it is natural here to utilize the approach based on tensor mathematics for them too. And creation of algorithms for work with tensor numeric objects on modern hybrid systems gets realized in a natural way.

In the last years, all best practice in CFD is concentrated in different enterprise toolkits from ANSYS and other companies. In majority, they utilize SPH approach or different models like RANS (Reynolds-averaged Navier–Stokes), Large-eddy simulation (LES) turbulence models, or hybrid models, such as detached-eddy simulation (DES) and scaleadaptive simulation (SAS) models that combine steady-state and LES treatments for the model's wall boundary layer and free shear portions, respectively.

2. GEOMETRIC SYNTHESIS OF COM-PUTATIONAL OBJECTS AND RELAT-ED ALGORITHMIC OPERATIONS

Let us consider the principles of construction of the computational objects in direct computational experiment. The described approach allows to partly automate the validation of code writing and to improve its computational efficiency. The geometrical construction of spatial problems includes scalar, vector and tensor numerical objects. Algorithmic procedures and arithmetic-logic operations are defined in the dimensional physical form and associate numerical objects and interpolation basis in a tensor mesh space.



Figure 1. Geometry of global space $\{\Omega\}$ and local basis $\{r(\omega)\}$; *i*, *j*, *k* – denote unitary vectors in the connected reference system

Elementary numerical objects are formed by non-coplanar basis vectors (Fig. 1). They serve to build indissoluble physical fields in the vicinity of adjacent mesh nodes ${}_{\Omega}^{T} \overrightarrow{R}$ and centers of mass ω . Products of vector and tensor quantities are performed with convolution, i.e. by summation over a^{j} repeated index in the monomial product ($a = a \cdot r$ or $a^{j} = a_{i} \cdot r^{ij}$), the transition to local basis and back ($a = a \cdot r$ or $a_{k} = a^{j} \cdot r_{jk}$). The latter occurs at the return to absolute coordinates.

The proposed notation is similar to that in [7] and [8]. The symbol notations and the principles of their construction are summarized below.

– A Left upper index marks the current time, which may be indicated by a capital letter ${}^{T}\Omega$ in absolute terms or the calculated step in time ${}^{t}R$. In addition, badges ${}^{+}\omega$ and ${}^{-}\omega$ designate links to the next or previous time interval.

- A Left low index marks a location in the mesh space $A_{X,Y,Z}$, r, or links to adducent knots A_{+} or centers of mass of liquid particles A_{-} . It is performed on conjugate stages of the computational experiment.

<u>Right indices</u> connect vector and tensor components in absolute and local bases. They serve to a strict definition of the

dynamics and deformation of numeric cells (particles of a continuous medium). - Low right indices, tensor "box" and $v_{ij}r^{jk} = \begin{pmatrix} v_{xx}r^{x} \\ v_{yx}r^{x} \\ v_{zx}r^{x} \end{pmatrix}$

- Low right indices, tensor "box" and $v_{ij}r - (v_{zx}r + v_{zj})$ the right arrow show the belonging to an absolute coordinate system (Fig. 1). For example, the tensor \hat{r} [m³] is a collection by columns of basis vectors \vec{r}_i in matrices of geometric transformations (like $\hat{a} = a \cdot r$ [m]).

– Upper right indices mark projections inside mobile and deformable mesh cells. The display of unitary vectors of absolute coordinates lies in row vectors in matrix of inverse coordinate transformations, $\mathbf{r} = r^{j} = r^{jk} = r^{-1} [\mathrm{m}^{-3}]$. They are marked by tensor "tick" and vector left arrow $\overleftarrow{a} = a \cdot \mathbf{r} [\mathrm{m}^{-2}]$.

- <u>Capital letters</u> are used for big numerical values measured in scale of global space (Ω) and general absolute time (T);

- <u>Lowercase letters</u> are used for especially small quantities or finite differences which are commensurable with the physical dimensions of local bases of particle continuum ω , as well as in the range of the current time step *t*.

The absolute time *T* can contain the Julian date and time from the beginning of the day¹: ${}^{k}T = T + k \cdot t$. Absolute values in space may also be presented²: $\overrightarrow{A} = \overrightarrow{R} + \overrightarrow{a} \cdot \overrightarrow{r}$ [m] (geographical and other generalized coordinates). The need of involvement of absolute encoder in space $\overrightarrow{\Omega}\overrightarrow{R}$ and time *T* is eliminated in the balanced numerical schemes. In this case, the use of numerical values at nodes and centers of mass of conjugate mesh cells is sufficient at all stages of calculations $\overrightarrow{r} = \overrightarrow{P} \overrightarrow{R} - \overrightarrow{O} \overrightarrow{R}$ [m³].

Kinematics of internal streams is defined by the speed difference tensor (Fig. 2). It is given on the large liquid particles basis vectors form shifted in time,

$$\stackrel{\wedge}{\mathbf{v}} \stackrel{\rightarrow}{t} = \stackrel{\rightarrow}{v_i} \cdot t = \stackrel{\Lambda}{{}_{\Delta}} \stackrel{\rightarrow}{r_i} = \stackrel{t}{{}_{+}} \stackrel{\rightarrow}{r_i} \stackrel{o}{{}_{\Omega}} \stackrel{\rightarrow}{r_i} \qquad [\mathrm{M}^3]$$



Figure 2. Movement of basis vectors³ of calculation cell in space

The tensor $\stackrel{\wedge}{v}$ [m³/s] defines the current speed of the displacement of the liquid particle basis vectors on a local scale (lowercase letters) that is measured in the projection of the global coordinate system (lower indices). The independent convective rates tensor describing the local motion of the fluid is obtained after transformation of the velocity tensor reference frame⁴ to the local basis of the large liquid particle (geometric normalization): $\stackrel{<}{v} = \stackrel{\wedge}{v} \cdot \stackrel{\vee}{r}$ [1/s].

The tensor (v) [1/s]) contains the extended set of kinematic elements of the differential equations with cross derivative components of deformable liquid particle motion:

$$x_{xy}r^{yx} + v_{xz}r^{zx} \quad v_{xx}r^{xy} + v_{xy}r^{yy} + v_{xz}r^{zy} \quad v_{xx}r^{xz} + v_{xy}r^{yz} + v_{xz}r^{zz} x_{x}v_{yy}r^{yx} + v_{yz}r^{zx} \quad v_{yx}r^{xy} + v_{yy}r^{yy} + v_{yz}r^{zy} \quad v_{yx}r^{xz} + v_{yy}r^{yz} + v_{yz}r^{zz} x_{x}v_{yy}r^{yx} + v_{zz}r^{zx} \quad v_{zx}r^{xy} + v_{zy}r^{yy} + v_{zz}r^{zy} \quad v_{zx}r^{xz} + v_{zy}r^{yz} + v_{zz}r^{zz}$$

Alternatively, such products can be presented in the form of complete differentiation $\stackrel{<}{v} = \stackrel{\wedge}{v} / \stackrel{\wedge}{r} = \stackrel{\Delta}{\omega} \stackrel{\vee}{v} / \stackrel{\Delta}{\omega} \stackrel{\rightarrow}{r}$ executed with-

$$\mathbf{v} \cdot \mathbf{a} = \mathbf{v} \cdot (\mathbf{a} \cdot \mathbf{r}) = \mathbf{v} \, \mathbf{r} \cdot \mathbf{a} = \mathbf{v} \cdot \mathbf{a} \, [\text{m/s}]$$

¹ The real time is set by the numeric structure Event with Julian data: D (from 4713 BC) and local time in hours from the day beginning: T

² In software environment points in global coordinates (Point) are separated with free vectors in local bases (Vector). It unifies computing operations with tensor numerical objects Tensor and Basis.

³ Tensors ω and v could be degenerate, and thus do not have a reciprocal.

⁴ Prohibition improving rank in product operation enables automatic permutation of factors in geometric transformations:

out artificial exceptions of "small" or convective elements in substantial derivative approximations. Thus correct physical interpretation of rheological characteristics of liquid and living conditions of currents is remained.

3. MATHEMATICAL FORMALIZA-TION OF CONTINUAL-CORPUSCULAR SIMULATION IN FLUID MECHANICS

Tensor mathematics is focused on the creation of direct computational experiments in solving practical problems of fluid mechanics. The continual-corpuscular approach is based on the numerical scheme of the first order with a consistent difference in the integration of the laws of motion of conjugate phases of scalar argument, i.e., time. Division of the computing stages by the physical processes enables continuous monitoring and hybrid evolution of mathematical relationships according to assessment of the current state of the simulated continuous medium, taking into account the intensity of the physical interaction between adjacent corpuscles as virtual numeric objects. The canonical representation of the laws of fluidmechanics allows strictly and unambiguously to associate numerical objects with arithmetic and logical operations and complex geometric algorithms, including the use of fast interpolation for unregularized grid spaces.

The consequent spatial integration of the first order involves grid and corpuscular approaches, formalized by means of the inertial mass tensor: $\mathbf{m} = m_k^i \, [\text{kg}]$ – which is used as a numeric object to fix pre-history, i.e., inertia in motion and local deformation of the simulated liquid particles that formed an algorithmic sequence of balanced prediction and correction of motion by a curved path for the fluid particles from the dynamically changing internal energy.

External mass force in the absolute coordinate system: \overrightarrow{f} [kg m/s²] – in vector interpretation of the second Newton law is represented by the derivative of the momentum: $\overrightarrow{r} \cdot \overrightarrow{r} = \frac{1}{2}$ $\overrightarrow{r} \cdot \overrightarrow{r} = \frac{1}{2}$

$$\overrightarrow{f} \cdot t = \overrightarrow{v} \cdot \overrightarrow{m} [N \cdot s]$$

At the stage of continuous matter of computational experiment the vector fields are specified by the absolute velocity of the free movement of fluid particles \overrightarrow{V} [m/s] – and the local velocity – \overrightarrow{v} [m/s] – under the influence of external mass forces \overrightarrow{f} [kg m/s²] with the internal energy and inertia of $\overrightarrow{m} = \overrightarrow{\rho} \cdot \overrightarrow{r}$ [kg] – of specific particle: \overrightarrow{r} [m³] – in the product with tensor $\overrightarrow{\rho}$ [kg/m³], which formalizes the prehistory actions of volume force of inertia and of surface complex of living forces – the inherent energy of a liquid corpuscle. The center of mass and any inclusions inside a corpuscle \overrightarrow{a} [m⁻²] – move in time t[s] in dependence on the environmental conditions \overrightarrow{m} [kg⁻¹] – in the vicinity of the nodes of the computational grid $\Omega \overrightarrow{R}$ [m] – inside the spatial cells \overrightarrow{r} [m⁻³]:

$$\mathbf{v} + \mathbf{v} = \mathbf{v} + \mathbf{f} / \mathbf{m} \cdot t$$
 [m³/s],

$$\stackrel{\rightarrow}{V} \stackrel{\rightarrow}{V} \stackrel{\rightarrow}{V} \stackrel{\rightarrow}{f} / \stackrel{\rightarrow}{m} \cdot t \qquad [m/s],$$

$${}^{+}\overrightarrow{A} = \overrightarrow{R} + {}^{+}\overrightarrow{V} \cdot t + \overleftarrow{a} \cdot (\overrightarrow{r} + {}^{+}\overrightarrow{v} \cdot t)$$
 [M],

where $\stackrel{+}{A}[m]$ – is the point location at new (next) time step; $\overrightarrow{R}[m]$ – is the original location of numerical cell center; $\overrightarrow{V}[m/s]$ – rate of free movement for a liquid particles; $\stackrel{\circ}{v}[m^3/s]$ - rotation and deformation tensor of the basis axes for the initial form tensor $\stackrel{\circ}{r}[m^3]$; $\stackrel{\circ}{f}[N m^2]$ – is the surface tensions tensor dynamically approximated by adjacent cells and boundary conditions.



Figure 3. Separation of the calculating stages by the physical processes includes tensor mass as a geometric operator which corrects the motion of the fluid particles by the Vis viva (inner energy) and inertia at the conjugate stages of simulations in the time

The conjugate corpuscular stage of computations generates an updated kinematic field of local velocities' trivectors $\stackrel{\wedge}{v}$ [m³/s] – specifying the deformation displacements relative to shifting corpuscles: $\stackrel{\wedge}{\varepsilon}$ [m³] – for reverse interpolation – secondary difference integration (Fig. 4) with fixing the tensions $\stackrel{<}{\sigma}$ [kg m²/s²] – in the immediate vicinity of the virtual numeric objects:

$$\overset{<}{\boldsymbol{\sigma}} = (\overset{\wedge}{\boldsymbol{\varepsilon}} \cdot \boldsymbol{\kappa} + \boldsymbol{v} \cdot \boldsymbol{\eta}) \times \lambda$$
 [N·m]

where $\stackrel{\vee}{\kappa}$ [N/m³] – tensor modulus of elastic deformation; $\stackrel{\vee}{\eta}$ [N s/m³] – tensor of viscosity coeffcients; λ [m] – the scale factor, which characterizes the distance between the interacting virtual energy objects – the large particles of liquid.



Figure 4. At the corpuscular stage of computational experiment an estimate of the current rheological state of the continuum in the initial nodes of the computational grid is made

Note that the tensors of tensions and local velocities may be degenerate. Change of basic sets without possibility of their inversion is performed only in multiplication operations with tensors of the form $\stackrel{\land}{v} \stackrel{<}{r} = \stackrel{<}{v} [s^{-1}]$ – or by algorithmic synthesis on the base of interpolation estimates of the environmental fluid state.

By analogy [6] inside the moving liquid particles a scalar function of the temperature distribution is involved, that is spread between the free particles by negative gradients; or change in the density of the elastic gas related to velocity of sound as function of the divergence of velocity and pressure values, including refinements imposed by the Bernoulli law and with the consideration of internal thermal energy, which

altogether synthesizes the extended solution of applied aeroand hydromechanics problems.

As the main loop in the computer experiment, the sequence of algorithms intended for matching kinematic and rheological characteristics of the physical field in explicit numerical schemes, reducible to the mode of sequential setting of nonstationary computational processes arising from mathematical models for viscous, elastic and compressible fluids is accepted.

REPRESENTATION 4. TENSOR OF THE BASIC LAWS OF FLUID ME-CHANICS

The formal construction of physical objects and operations in the tensor mathematics [7] leads to strict definitions for the kind of "model of world" of computational fluid mechanics: 1) continuous corpuscular computing model of the method of "large particles" [2] in the tensor recording is reduced to a double linear difference interpolation of the physical fields (instead of integrating the equations of motion of the second order); 2) the movement and interaction of large liquid particles is built in terms of the operations of the product that more precisely corresponds to the physics of spatial processes (there are no restrictions on the smallness of the differential approximation); 3) the use of explicit numerical schemes and of discrete numeric fields serves to increase the effectiveness of direct computational experiments, and do not exclude the possibility of monitoring the correctness and, if necessary, involving of hybrid schemes to achieve adequate engineering results of direct numerical simulation.

The law of motion for a particle continuum:

$$\overrightarrow{f} = \overrightarrow{w} \cdot \overrightarrow{m} = \overrightarrow{w} \cdot \overrightarrow{\rho} \cdot \overrightarrow{r} .$$
 [N]

The Newton's viscous stress tensor:

$$\stackrel{<}{f}_{N} = \stackrel{\wedge}{\boldsymbol{v}}_{N} \cdot \stackrel{\vee}{\boldsymbol{\eta}} \lambda = \stackrel{<}{\boldsymbol{v}}_{N} \cdot \stackrel{<}{\boldsymbol{\eta}} \lambda . \qquad [N/m]$$

The Hook's elastic stress tensor:

$$\int_{H}^{<} = v H \cdot \vec{k} \cdot t / \lambda = v H \cdot \vec{k} \cdot t / \lambda , \qquad [N/m]$$

wherein the tensor of local velocities $\stackrel{\wedge}{v} = \stackrel{+}{_{+}} \stackrel{\rightarrow}{_{v}} \stackrel{o}{_{o}} \stackrel{\rightarrow}{_{v}} \stackrel{i}{_{v}}$ (Fig. 2); rheological tensors $\stackrel{>}{m} = \stackrel{\vee}{\rho} \cdot \stackrel{\wedge}{r} [kg]$ – tensor of mass inertia; $\stackrel{\wedge}{r}$ [m³] – tensor of form; $\stackrel{\vee}{\rho}$ [kg/m³] – "conditional density" of saving the pre-history of deviations - internal Vis viva (local forces) of moving corpuscles; η [kg/m²/s] – tensors of dynamic viscosity and stiffness κ [kg/m²] of real fluid; λ – short distance interaction of adjacent particles.

The computational model comprises rheological properties of the fluid: viscosity and elasticity, while the ratio of the intensities of the resulting tensions determines the appearance of the critical flow regimes with the formation of jets, vortex layers and cavitations breaks. Under the influence of the internal stress tensor, a fluid particle gets velocity increment to internal (closed) movement which is traditionally represented by three dynamic states:

$$\begin{split} \hat{\vec{f}} &= \hat{\vec{v}}_{0} \cdot \stackrel{\checkmark}{\varepsilon} \cdot t + \stackrel{\land}{v}_{N} \cdot \stackrel{\lor}{\mu} / \lambda + \stackrel{\land}{v}_{H} \cdot \stackrel{\lor}{\kappa} \cdot t / \lambda = , \quad \text{[H/M]} \\ &= \stackrel{\checkmark}{f}_{0} + \stackrel{\checkmark}{f}_{N} + \stackrel{\checkmark}{f}_{H} \end{split}$$

where the tensor $\stackrel{<}{f}_0$ is the pressure, $\stackrel{<}{arepsilon}$ is the compression ratio. The dynamic coefficients $\stackrel{\vee}{\mu}, \stackrel{\vee}{\kappa}, \stackrel{\vee}{\epsilon}$ differ from the kinematic ones by elimination of the scalar density value ρ . The resulting characteristic polynomial is used to assess the state of the liquid where the rheological parameters appear as the main invariants of the tensor of the convective velocities:

- $\stackrel{<}{v}_0$: I \neq 0 compressibility \rightarrow cavitation density gap;
- $\stackrel{<}{\mathfrak{v}}_{N}$: II \neq 0 turn \rightarrow formation of free jet or turbulent vortex;
- $\hat{\mathbf{v}}_{H}$: III $\neq 0$ deformation, net \rightarrow if the other invariants of the tensors are zero.

For example, if the computed cell with an attached vortex makes the determinant of internal field of convective velocities equal to zero in a conjugated point, i.e., in the point at the center of mass of free conjugate liquid particle, that will determine the emergence of a free turbulent vortex inside a large liquid particle. Such hybrid algorithm can be used either outside the approximated resolution for relatively coarse grids, or to improve decisions when the grid area in the zone of vortex shedding should condense.

5. ON PECULIARITIES OF THE TEN-SOR GENERALIZATION OF APPLIED FLUID MECHANICS PROBLEMS

At stages of computing experiment the velocity field ω [m³/s] is formalized with a potentially degenerate tensor that satisfies the traditional additive construction of the flow model $\stackrel{+}{r}=^{o}\stackrel{\wedge}{r}+\stackrel{\wedge}{v}\cdot t$ [m³] – in absolute time: t [s]. The definition of the tensor - affinor and expansion of Cauchy-Helmholtz [8] for spatial displacement is true: expansion (divergence); twist (rotor) and the deformation (shear).

Discrimination of the ball (diagonal) tensor $\stackrel{<}{\mathbf{v}_{o}}[s^{-1}]$ – such that the trace of the deviatory residue: tr $\stackrel{<}{\nu}_{\nu}^{*}$ – would be equal to zero [9]:

$$\overset{<}{\nu} = \overset{<}{\nu}_{0} + \overset{<}{\nu}^{*} (\text{tr } \overset{<}{\nu}^{*} = 0) \qquad [\text{c-}^{1}];$$

$$\boldsymbol{\sigma} = \boldsymbol{\varepsilon} \cdot \boldsymbol{v}_0 \cdot \boldsymbol{t} \qquad [N],$$

where tensor determinant $\stackrel{<}{\sigma}$ – determines the pressure, $\stackrel{<}{\varepsilon}$ – volume compression ratio - Young's modulus.

Symmetrization of deviatory tensor v^{+}_{μ} - sets the shear stress

$$\tau_H$$
 [N/m²] – according to Hooke's law within
the large particle continuum:

$$\boldsymbol{\tau}_{H} = \boldsymbol{c} \cdot \boldsymbol{v}_{H} \cdot \boldsymbol{t} = \boldsymbol{c} \cdot (\boldsymbol{v}^{*} + \boldsymbol{v}^{*T}) \cdot \boldsymbol{t}/2 \quad [N]$$

the elastic modulus $\overset{<}{\boldsymbol{c}} [N/m^{2}]$ and symmetric tensor

with with respect to local displacements within a large fluid particle $\vec{v}_H \cdot t$.

Skew-symmetric superposition with the components of the deviatory tensor separates the initial impulse to the rotation

of the liquid particles, with the emergence of stress τ_N^{-} in Newtonian definition of a viscous liquid mechanics: $\tau_N^{-} = \eta \cdot v_N^{-} = \eta \cdot (v - v^{+})/2$ with the viscosity coefficient matrix $\stackrel{<}{\eta}$ [N s/m³] – in a product with the tensor of local deformations velocities $\stackrel{<}{\nu}_{N}$ [c⁻¹]. The rheological characteristics of the state of liquid $\stackrel{<}{\varepsilon}$ [N/m²], $\stackrel{<}{c}$ [N/m²] and $\stackrel{<}{\eta}$ [N·s/m²] – can be defined by scalar coefficients in the traditional relationship between stress, local deformations and viscose movements of the continuous medium. In the tensor generalization the anisotropy of practical cross–linking components in the rheological characteristics of the liquid is implicitly taken into account by means

Tensor mathematics completely covers the traditional models for linking internal stress with small displacements and strain velocities:

$$\overset{<}{\boldsymbol{\varphi}} = \overset{<}{\boldsymbol{\sigma}} + \overset{<}{\boldsymbol{\tau}}_{H} + \overset{<}{\boldsymbol{\tau}}_{N} = (\overset{<}{\boldsymbol{\varepsilon}} \cdot \overset{<}{\boldsymbol{v}}_{0} + \overset{<}{\boldsymbol{c}} \cdot \overset{<}{\boldsymbol{v}}_{H}) \cdot t + \overset{<}{\boldsymbol{\eta}} \cdot \overset{<}{\boldsymbol{v}}_{N}$$

In order to bring the law of motion with inertial mass $\stackrel{<}{f} \cdot t = \stackrel{<}{m} \cdot v$ [kg/s] – to the new relationships for the surface tension $\stackrel{<}{\varphi}$ [kg/m/s²], the factor with the dimension of the space vector is necessary, that corresponds by the physical meaning either to the vector of direction of movement for Zhukovsky theorem for the free vortex dipole, or to the distance between the interacting particles of liquid.

6. CONCLUSION

of Poisson's coefficients.

The geometrical construction of non-regularized grid spaces [10] in explicit numerical schemes of the first order for the sequential integration in conjugated stages in continuous-corpuscular computing experiments when modeling the transient processes in fluid mechanics is represented by sequential superposition upon the architecture of digital computers: 1. A continual corpuscular division of the stages of the computing experiment in fluid mechanics is constructed in the continuity space of physical values, initially defined in a single absolute coordinate system using scalar, vector and tensor characteristics of the state and the laws of transformation of the mobile and deformable continuous medium;

2. In multiplication operations with external (mass) and internal (surface) tensions for the computed time interval, the internal state of each computed cell is rebuilt in the similitude of the estimated independent large fluid particle accumulating internal energy and making influence on the kinematic reactions in the interpolation rebuilding of updated physical fields in the initial computational nodes;

3. In dealing with very complex physical laws of fluid mechanics, an additional third phase of calculations is introduced for monitoring and adjusting the internal state of the liquid particles, with the coordination of the laws of conservation of the mass and momentum of the free liquid particles from the point of alignment the calculations at the two main stages of the computational experiment for the scalar argument, the time.

7. ACKNOWLEDGEMENT

The research is partly supported by Russian Foundation for Basic Research (projects N 16-07-01113, 16-07-00886, 17-29-04288).

REFERENCES

- A.A. Dorodnitsin, "Selected works", Publication of the Computer Centre of the Academy of Sciences Russia, V.1.2, Moscow, 1997.
- [2] O.M.Belotserkovsky, Yu.M. Davydov, "Method of large particles in the gas dynamics", *Nauka*, Moscow, 370 p, 1982.
- [3] G. Astarita, G. Marrucci, "Principles of non-Newtonian fluid mechanics", *McGRAW-HILL Book Company*, UK, 289 p, 1974.
- [4] B.S. DeWitt, "Dynamical theory of groups and fields", Gordon and Breach, N.-Y., 264 p, 1965.
- [5] Manin Yu., Gauge Field Theory and Coplex Geometry. (Springer – Verlag, Berlin, 1997) 289 pp.
- [6] M.E. Eglit, "The lectures on the basics of continuum mechanics", *Publishing house of the Moscow Universi*ty, Moscow, 318 p, 2008.
- [7] V. N. Khramushin, "Three-dimensional tensor mathematics of computational experiments in fluidmechanics", *FEB RAS*, Vladivostok, 212 p, 2005.
- [8] A.Sh. Gotman, "The tensor calculus", Novosibirsk State Academy of Water Transport, Novosibirsk, 129 p, 2007.
- [9] A.J. Mac-Konnel, "Introduction to tensor analysis", *Dover Publications*, 352 p, 2011.
- [10] P. Wesseling, "Principles of Computational Fluid Dynamics", Springer Series in Computational Mathematics, 644 p, 2001.